

DECLARATION OF PERFORMANCE

in accordance with Annex III to Regulation (EU) No 305/2011 for the product

SICOROL C

1. Unique identification code of the product type:

EN 1504-2: ZA.1a

2. Type-, batch- or serial number or any other means of identification of the construction product in accordance with Article 11(4):

batch number: see packaging of the product

3. Intended use or uses of the construction product as foreseen by the manufacturer in accordance with the applicable harmonized technical specification:

Surface protection products - water-repellent impregnation
Protection against the penetration of substances (1.1)
Regulation of the moisture content (2.1)
Increase of the electrical resistance (8.1)

4. Name, registered trade name or registered trademark and contact address of the manufacturer in accordance with Article 11(5):

FABRINO Produktionsgesellschaft mbH & Co. KG
Augsburger Straße 23
D-87700 Memmingen

5. Where appropriate, the name and contact address of the authorized representative responsible for the tasks referred to in Article 12(2):

not relevant

6. System or systems for assessment and verification of constancy of performance of the construction product in accordance with Annex V:

System 4

7. In the case of a declaration of performance concerning a construction product covered by a harmonized standard:
With the certificate of factory production control, the notified body [KIWA Polymer Institut GmbH, identification number [1119] certifies that all provisions concerning the assessment and verification of constancy of performance described in Annex ZA of harmonised standard EN 1504-7, edition 11/2006 have been applied.

1119-CPR-14145

8. In the case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not relevant


9. Declared performance:

Essential characteristics	Performance	Harmonized Technical Specification
Weight loss after alternating exposure to freeze-thaw and de-icing salt EN 13851	compared to the unimpregnated specimen, 20 cycles later	EN 1504-2:2004
Water absorption and alkali resistance EN 13580	Absorption coefficient < 7.5 %, compared to the untreated Absorption coefficient, Absorption coefficient < 10 %, after immersion in alkaline solution	
Penetration depth EN 1504-2 Tab. 3	Class II: ≥ 10 mm	
Drying rate EN 13579	Class II: > 10 %	
Dangerous substances	NPD	

10. The performance of the product referred to in points 1 and 2 corresponds to the declared performance referred to in point 9. The manufacturer referred to in point 4 is solely responsible for drawing up this declaration of performance.

Signed for the manufacturer and on behalf of the manufacturer of:

Memmingen, 25.09.2018


Dr. Klaus Hörmann

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006 (REACH), Annex II is annexed to this Declaration of Performance.